


	<p>Date Issued: March 22, 2011</p>
<p>Product Use</p> 	<p>The 3M™ QS1000 Full Page Reader inspects and images Machine Readable Travel Documents (MRTDs) in a variety of market segments.</p> <p>This includes applications that are primarily focused on data capture opportunities in hotels, casinos, liquor stores, bars, and rental car companies.</p>
<p>Key Standard Features & Functionality</p>	<ul style="list-style-type: none"> • Multiple document reading and imaging capability – imaging in 24-bit color • 400 DPI high resolution imaging • Scanning window 88mm x 125mm • Multiple wavelength illumination – visible and IR • OCR data capture • Complete access to OCR data and images captured via Software Development Kit (SDK) • Enables images to be accessed as BMP, PNG or JPEG format • Auto-triggering of document capture – presence of document is automatically detected • USB 2.0 high speed compatible • No moving parts and comes with an IP50 rating for dust ingress protection
<p>Comprehensive Software Features</p>	<ul style="list-style-type: none"> • Flexible software interface allows host application to select which illumination sources to use, image type, image compression, photo extraction etc. • Simple high level API for quick program development or detailed low level API for fine control of all reader functions • SDK provides full configuration API
<p>Reading Capability</p>	<p>The 3M™ QS1000 Full Page Reader reads the following:</p> <ul style="list-style-type: none"> • ICAO compliant documents in near infrared (IR) per ICAO 9303 specification Parts 1-4 • 1D barcodes (2 of 5 interleaved, Code 128, and Code 39) • 2D barcodes (PDF 417, QR, DataMatrix™ and Aztec formats) from paper documents and most mobile devices

Illumination	<p>The reader illuminates documents in multiple wavelengths</p> <ul style="list-style-type: none"> • Near IR B900, 880nm, +/-5% • White visible, 430-700nm
Resolution	<ul style="list-style-type: none"> • Sensor: 3.1 Megapixels, CMOS, RGB 24 bit color system • Standard 400 DPI image resolution
Firmware Upgrade	<ul style="list-style-type: none"> • Upgradeable firmware via USB 2.0 interface • Configurable via USB 2.0 interface • Non-volatile configuration • Configuration can be saved to a file for backup or maintenance
Regulatory	<ul style="list-style-type: none"> • FCC Part 15 Class A • UL, UL-C • CE, CB • WEEE/RoHS¹
Operating Environment	<ul style="list-style-type: none"> • Humidity: 20 to 95% (R.H. non-condensing) • Temperature: 0° to 50° C operating; -20° to 50° C storage
Security	<ul style="list-style-type: none"> • Keystone lock
Minimum PC Specification	<p>Software must be installed on a customer-supplied PC. The following <i>minimum</i> configuration is recommended to maintain the processing speed indicated above:</p> <ul style="list-style-type: none"> • 1.7 GHz Pentium 4 • 512 Mb DRAM • USB 2.0 High Speed • 100 Mb of Hard Drive space for software • Windows® 2000-SP4, Windows® XP, Windows Vista® or Windows® 7 operating systems, 32 and 64 bit
Standard Dimensions	<ul style="list-style-type: none"> • Length: 19.0 cm (7.5") • Width: 16.2 cm (6.4") • Height: 15.7 cm (6.2") (with light shield) • Weight: < 1 kg or 2.2 lbs

¹ RoHS compliant means that the product or part does not contain any of the following substances in excess of the maximum concentration values in any homogeneous material, unless the substance is in an application that is exempt under RoHS, as amended: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. This information represents 3M's knowledge and belief, which may be based on information provided by third party suppliers to 3M

<p>Status Indicators</p>	<p>The reader provides user feedback via the following status indicators:</p> <ul style="list-style-type: none"> • Red - Read Error LED • Blue - Ready LED • Yellow - Busy LED • Green - Valid Read LED <p>The reader performs a power-up self-test and indicate failure using status LEDs.</p>
<p>Power</p>	<p>USB Powered</p>
<p>Service & Maintenance</p>	<ul style="list-style-type: none"> • One-year warranty • 24-hour service request via toll-free number • Annual maintenance agreement available
<p>Contact 3M</p>	<ul style="list-style-type: none"> • Middle East Sales & Support- www.opentecme.com <p>Opentec Systems LLC - 3M Security Systems Division P O Box 31720 Dubai - United Arab Emirates. Tele: 971 4 28 222 63 - Email: mk@opentecme.com</p>

Important Notice to Purchaser: 3M Security Systems Division offers a range of security products to protect against article and/or document identity counterfeit, alteration, diversion, duplication, simulation and substitution. However no security products can guarantee absolute protection against attempts to successfully accomplish these illegal activities. For specific 3M products and solutions, please see 3M.com/security.

Warranty, Limited Remedy and Limited Liability:

THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. 3M warrants that the 3M™ QS1000 Full Page Reader will be free from defects in material and manufacture for 12 months from the date of shipment. 3M's obligation and your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **IN NO EVENT WILL 3M BE LIABLE FOR ANY INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES INCLUDING, BUT NOT LIMITED TO LOSS OF PROFITS, IN ANY WAY RELATED TO THE PRODUCTS REGARDLESS OF THE LEGAL THEORY ASSERTED.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Warranties, remedies and limitations may vary by product and jurisdiction. Please consult 3M product quote or agreement, or contact 3M for specific information about individual products.

3M and Confirm are trademarks of 3M Company.

Windows, Windows Vista, Visual C++, and Visual Basic are registered trademarks of Microsoft Corporation in the United States and other countries. Java is a registered trademark of Oracle and/or its affiliates. Pentium is a registered trademark of Intel Corporation. Data Matrix is a trademark of Robotic Vision Systems, Inc. (RVS).